

2023 Light Mod Rules

1. No loaded frames, No welding frame holes shut. NO painted frames!! Frames will be scoped and drilled if necessary!!
2. Full cradles, DP's and trans braces allowed. 2-2x2x1/4" kickers from dash bar to back side of upper A-arm if DP is not used or fire wall is cut completely out.
3. Stock A-arms and spindles must be used but may be swapped from other vehicles, aftermarket tie rods, ball joints, etc.. may be used. A-arm may be welded down.
4. Absolutely no doubled body panels , except for Drivers door skin, allowed to overlap door seam 2".
5. Any bumper allowed as long as point is no larger 14" and spread out over 32". May be mounted 1" from front body mount bracket.
6. May have 1- 4"x8"x1/4" plate on side of frame from back of bumper down front horn.
7. All bolt ins allowed but cannot attach to frame or strengthen car in anyway.
8. Rear Hump plates allowed, no more than 22" long.
9. Rear frame rails may not be shortened , bumper brackets must be 12" from hump plates unless it's a factory bracket.
10. Good Mod cages allowed, may be inside doors, side bars may go to wheel tubs, 4 down tubes(no material larger than 4") straight down from cage to frame, gas tank protector may be tight against rear package tray but not attached in anyway, no wider than 36".
11. Body mounts may be replaced with 1" spacers and 1/2" bolts for body bolts. Allowed 6 (3 per frame rail) pieces of 3/4" althread 30" long going through frame and body. This includes the 2 althreads in core support.
12. Any wheel and rubber tire allowed.
13. (6) 4"x6"x 1/4" max patch plates allowed. May be used anywhere on frame but must have 1/2" gap between welds from touching, no cutting them to make longer. Cannot attach from frame to body or any other combo.